



Notes:

- Pitch: 3.81mm Poles: 2-20P
- Rated voltage/current: UL 300V/8A
VDE 250V/12A
- Operation temperatures: $-45^{\circ}\text{C} \sim +105^{\circ}\text{C}$
- Withstanding voltage: AC2000V/1Min
- Insulation Resistance: $5000\text{M}\Omega / \text{DC}1000\text{V}$
- Wire range: 28-16AWG, 0.2-1.5mm²
- Undimensioned Tolerances:

Pitch range in mm		Nominal dimension range in mm						
to	over	to	to	to	to	to		
6	6	10	10	30	60	100	150	∩
6	10	24	30	60	100	150		□
± 0.10	± 0.15	± 0.25	± 0.2	± 0.3	± 0.5	± 0.7	± 1.0	0.05/10

ITEM	DESCRIPTION	PART NO.	QTY	MATERIAL	REMARKS
6	2EDG M2.5"-Screw	S00000980 (H)	2	steel	Cr ³⁺ Zn
5	15EDGKD spring	X00001310 (H)	XX	stainless steel	
4	15EDGKD PIN	1088B00010 (H)	XX	phosphor bronze	Snce plated
3	15EDGKD BUTTON	1088D0501A (H)	XX	PA66	UL94V-0
2	15EDGKD-3.81-COVER	1088C0YXXA (H)	1	PA66	UL94V-0

ITEM	NAME OF PART	NO. OF PART	Q"TY	MATERIAL	NOTES
1	15EDGKDM-3.81-HOUSING	1102A0YXXA (H)	1	PA66	UL94V-0

MM (INCH)	DFTO Zhwm	DATE 05/31/07	宁波高正电子有限公司 DEGSON ELECTRONICS CO., LTD
TOLERANCES EXCEPT AS NOTED	CHKD	DATE	
	MFO	DATE	
	APPVL	DATE	
MM			NAME
.0 ±	±		15EDGKDM-3.81-XXP-1Y-00A(H)
.00 ±	±		DRAWING NO. 15EDGKDM-3.81-E01
.000 ±	±		/PART NO.
ANGLES ± 1°	G.E :		SIZE
	FINISH :		A3
THIRD ANGLE PROJECTION	SCALE :		REV T5
			10/21/10
		DO NOT SCALE DRAWING	SHEET 1 OF 1