



REVISION RECORD				
REV	ECO	DESCRIPTION	DRFT	DATE
△	10-017	增加UL刻字	Jordan.Yuan	06.07.10
△	10-0274	修改外形避专利	HD	08.20.10
△	10-0304	增加VDE CE刻字	HD	09.15.10

- Notes:
- pitch:10.16mm, ploes:2-8p
 - Rated current/voltage:
UL 52A/600V
VDE 57A/600V
 - Operation temperatures:-40° ~+105°
 - Withstanding Voltage:AC3500V/1min
 - Insulation Resistance:5000MΩ/DC1000V
 - Undimensioned Tolerances:

Pitch range in mm		Nominal dimension range in mm										
to	over	to	over	to	over	to	over					
6	6	10	10	30	30	60	60	100	100	150	150	□
±0.10	±0.15	±0.25	±0.2	±0.3	±0.5	±0.7	±1.0	0.05/10				

2	5EDGRC-10.16-Pin	1194B00010(H)	XX	Copper	Ag plated
---	------------------	---------------	----	--------	-----------

1	5EDGRC-10.16-Housing	1194A0YXXA(H)	1	PA66	UL94V-0	
ITEM	NAME OF PART	NO. OF PART	Q"TY	MATERIAL	NOTES	
MM (INCH)	DFTO Zhwrm	DATE 09/05/08"	宁波高正电子有限公司 DEGSON ELECTRONICS CO., LTD NAME 5EDGRC-10.16-XXP-1Y-00A(H) DRAWING NO. 5EDGRC-10.16-E01 /PART NO. SIZE A3 REV T3 09/15/10"			
TOLERANCES EXCEPT AS NOTED		CHKD				DATE
MFO		DATE				
APPLV		DATE				
MM	±	MATERIAL :				
.0 ±	±	G.E :				
.00 ±	±	FINISH :				
.000 ±	±	SCALE : 1:1				
ANGLES ± 1°		DO NOT SCALE DRAWING		SHEET 1	OF 1	
THIRD ANGLE PROJECTION						