






DEGSON ELECTRONICS CO., LTD.

Product Specification




DG65C-A



Poles	2	3	4	5	6	7	8	9	10	11	12	13	14	15
L(mm)	24.00	35.00	46.00	57.00	68.00	79.00	90.00	101.00	112.00	123.00	134.00	145.00	156.00	167.00
S(mm)	11.00	22.00	33.00	44.00	55.00	66.00	77.00	88.00	99.00	110.00	121.00	132.00	143.00	154.00
Poles	16	17	18	19	20	21	22	23	24	25	26	27	28	
L(mm)	178.00	189.00	200.00	211.00	222.00	233.00	244.00	255.00	266.00	277.00	288.00			
S(mm)	165.00	176.00	187.00	198.00	209.00	220.00	231.00	242.00	253.00	264.00	275.00			

Approval	UL US	CE
Electrical	UL	IEC
Standard	300V	750V
Rated voltage	20A	32A
Rated current	22-12AWG	4.0mm ²
Wire range	AC2000V/1Min	
With standing voltage	500MΩ/DC500V	
Insulation Resistance		
Mechanical		
Max. Torque Value	1.2N.m 10.6Lb.in	
Ambient temperature	-40°C → +105°C	
Dimensions		
Pitch	11.0mm (.433")	
Poles	2P-20P	
Material		
Housing	PA66, UL94V-0	
Terminal	Brass, 0.8t, Tin Plated	
Screws	Steel, M4 Ni Plated	

HOW TO ORDER :



	DEGSON ELECTRONICS CO., LTD.
	NAME DG65C-A